


# PRV

PATENT- OCH REGISTRERINGSVERKET

Patentavdelningen



PCT / SE 2004 / 0 0 0 0 7 0

## Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

*This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.*



(71) Sökande Carmel Pharma AB, Göteborg SE  
Applicant (s)

(21) Patentansökningsnummer 0300155-9  
Patent application number

(86) Ingivningsdatum 2003-01-21  
Date of filing

Stockholm, 2004-02-05

För Patent- och registreringsverket  
For the Patent- and Registration Office

*Marita Öun*  
Marita Öun

Avgift  
Fee

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

PATENT- OCH  
REGISTRERINGSVERKET  
SWEDEN

Postadress/Adress  
Box 5055  
S-102 42 STOCKHOLM

Telefon/Phone  
+46 8 782 25 00  
Vx 08-782 25 00

Telex  
17978  
PATOREG S

Telefax  
+46 8 666 02 86  
08-666 02 86

**A needle for penetrating a membrane**

Huvudfaxen Kassac

**FIELD OF THE INVENTION**

5 The present invention relates to a needle for penetrating a membrane in accordance with the preamble of claim 1, an arrangement for transferring a liquid in accordance with the preamble of claim 15, a needle for penetrating a membrane in accordance with the preamble of claim 29 and a method for manufacturing a needle for penetrating a membrane in accordance with the preamble of claim 33.

10

The invention is applicable in several different technical fields of use when a membrane is penetrated, but hereinafter for illuminating, but not in any way restricting, the invention, the use when a membrane is penetrated for transferring a liquid, such as a medical substance, from a needle to a container which is sealed by the membrane or for transferring a liquid  
15 from the container to the needle, by means of the needle, will be described.

**BACKGROUND OF THE INVENTION**

20 Known needles for suction and injection of medical substances, which needles have a flow direction which is substantially parallel to the longitudinal extension of the needle, i.e. the liquid flows out from or into the needle in a main direction which is substantially parallel to the longitudinal centre line of the needle, are primarily used for injection of pharmaceutical preparations into a patient or for drawing of blood from a patient. In such cases, the needle penetrates the skin and the tissues directly under the skin and there is a strong-felt desire  
25 that the penetration may be performed while causing as little pain as possible for the patient. For this reason, the needles are designed to require as small a force as possible when the skin is penetrated and this may be achieved by the needle being ground so that the penetrating tip of the needle has sharp edges which cut an incision in the skin, through which incision the needle is inserted into the body of the patient.

30

Traditionally, needles of the type discussed above are also used for penetrating a membrane when medical substances are handled. Such membranes are frequently used in medical systems, for example as a seal of a container, such as medicine bottles or similar. In this connection, the needle has two functions; the needle shall penetrate the membrane, and the  
35 needle shall transport the substance. However, these needles have important drawbacks due

35

to the fact that sharp edges of the tip of the needle may release particles from the membrane. This effect is called "coring" and is primarily initiated from sharp inner edges of the lumen of the needle. A core from the membrane, made of rubber for instance, could be produced when the needle penetrates the membrane. These cores or particles may be carried by the needle and contaminate the substance transported via the needle. Further problems arise as a consequence of the fact that the needle leaves a cut in the membrane when the membrane is penetrated, which cut has an extension corresponding to substantially the width of the edge of the needle. One or more such cuts of the membrane may result in the membrane not being able to fit tightly around the needle and, thus, leakage may arise. When medical substances are handled, it is often an absolute condition that leakage does not arise, since in the case of a leakage, the substance may be contaminated and/or spread to the environment. Furthermore, after several penetrations, parts of the membrane may be released, i.e. may be cut away, from the membrane and contaminate the current substance.

Some known needles have been developed taking into account the aspect of avoiding coring from a sharp inner edge of the lumen of the needle by mechanical blasting treatment thereof. However, since the needle must have a sharp outer edge on the tip of the needle to obtain good penetration properties as discussed above, and the needles are mass-produced, the needles are manufactured to obtain the best penetration and cutting properties at the expense of the anti-coring properties, i.e. it is not possible to blast the outermost part of the tip because in that case the cutting properties of the needle are impaired.

## THE OBJECT OF THE INVENTION AND SUMMARY OF THE INVENTION

A first object of the present invention is to provide a needle of the kind defined in the introduction, which needle will reduce at least one of the drawbacks discussed above of already known such needles to a substantial extent, i.e. a needle which reduces the risk that a leakage arises and/or that particles from the membrane are released.

This object is attained according to the invention by a needle according to appended claim 1.

Due to the fact that the penetrating tip is designed with a substantially point-shaped edge to initially prick the membrane when the membrane is penetrated and that the outer edges present on the pointed end in the area between the point-shaped edge and a position

beyond the opening are rounded so that after the initial penetration the pointed end will push the membrane material away rather than cutting the membrane material, ideally, a point-shaped hole without cut cuts of the membrane will be obtained when the membrane is penetrated. The absence of cut cuts of the membrane reduces the risk that leakage arises and that parts of the membrane will be removed when the membrane is penetrated. Furthermore, the rounded outer edges of the pointed end, i.e. a dulled tip, enable the needle tip to slide on the membrane to a penetration hole which originates from a previous penetration, without cutting the membrane, when penetration of the membrane is repeated, thereby causing the needle to be self-centring and to penetrate the membrane through the already existant hole, which even more reduces the risk that leakage arises and that parts of the membrane will be removed when the membrane is penetrated.

According to a preferred embodiment of the needle according to the invention the inner edge of the opening is rounded. Such a rounded inner edge further decrease the problem of coring membrane material when the needle penetrates a membrane.

According to another preferred embodiment of the needle according to the invention the penetrating tip is designed with a cross section having a symmetry causing at least three substantially equally sized forces in different directions which are radial to the longitudinal centre lines of the needle and which forces counteract each other so that the needle will tend not to deviate from the initial penetration direction when the needle penetrates a membrane. The provision of such a symmetric cross section of the penetrating tip enables the needle to follow the initial penetration direction during penetration, i.e. the needle becomes self-centring, and, thus the risk of releasing material from the membrane is decreased.

Sve. t. Patent- och reg.verket

4

2003 -01- 2 1

Fluvudföreläsningen

According to another preferred embodiment of the needle according to the invention, preferably in combination with the cross section discussed above, the penetrating tip is arranged to lie substantially on the longitudinal centre line of the needle. Hereby, the needle  
5 may impact the same point of the membrane in every penetration even in the case when the needle is rotated about its longitudinal axis between penetration occasions and the needle becomes self-centring, and a favourable load distribution on the membrane is obtained during penetration thereof, thereby reducing the risk of the membrane cracking adjacent to the penetration hole. Furthermore, the transport of membrane material into the needle  
10 through the opening of the needle is further obstructed.

A second object of the present invention is to provide an arrangement of the kind defined in the introduction, for transferring a liquid, in which arrangement the risk of contaminating the liquid and/or spreading the liquid to the environment has been reduced to a substantial  
15 extent.

This object is attained according to the invention by an arrangement according to appended claim 15.

20 The invention also relates to a needle according to claim 29. Provision of such a symmetric cross section of the penetrating tip enabling the needle to follow the initial penetration direction during the penetration and, thus, the risk of releasing material from the membrane is decreased.

25 According to another preferred embodiment of the needle according to claim 29, the penetrating tip is arranged to lie substantially on the longitudinal centre line of the needle. Hereby, the needle becomes even more self-centring and a favourable load distribution on the membrane is obtained during penetration thereof, reducing the risk of the membrane cracking adjacent to the penetration hole. Furthermore, the transport of membrane material  
30 into the needle through the opening of the needle is further obstructed.

A further object of the present invention is to provide a method enabling that a needle according to the invention for penetrating a membrane may be manufactured in a rational way and at a low cost.  
35

This object is attained according to the invention by a method according to appended claim 33.

# BRIEF DESCRIPTION OF THE DRAWINGS

5

Hereafter, preferred embodiments of the invention will be described by way of example only and with reference to the attached drawings.

In the drawings:

10

Fig. 1 is an elevational view of a part of a needle according to the invention together with a schematic membrane,

Fig. 2 is a view from above of the needle in Fig. 1,

15

Fig. 2a is a sectional view of the penetrating tip of the needle in Fig. 2,

Fig. 3 is a schematic plan view of a membrane which has been penetrated by a needle designed in accordance with prior art,

20

Fig. 4 is a schematic plan view of a membrane which has been penetrated by a needle designed in accordance with the invention,

Fig. 4a is a schematic plan view of a membrane which has been penetrated at different locations by a needle designed in accordance with the invention,

25

Fig. 5 is an elevational view of a part of a blank for manufacturing a needle according to the invention,

30

Fig. 6 is an elevational view corresponding to the view in Fig. 5 illustrating how the tip of the needle has been brought into a position so that it intersects the longitudinal centre line of the needle,

Fig. 7 is a view from above of the blank illustrated in Fig 5,

35

Fig. 8 is a view corresponding to the view in Fig. 6 illustrating an example of a needle according to the invention provided with a suitable cut before the needle is finally surface treated for further shaping and removing of possibly sharp edges and burrs,

5 Fig. 9 is a view from above of the needle illustrated in Fig. 8, and

Fig. 10 is a sectional view of the needle in Fig. 9.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

10

In Figs. 1 and 2, a needle 1 for penetrating a membrane 2 is illustrated. The needle 1 has a pointed end 3 provided with a penetrating tip 4. The outermost portion of the penetrating tip 4 is arranged to lie substantially on the longitudinal centre line 5 of the needle 1, i.e. the outermost portion is located on or very close to the centre line 5. Since the tip 4 is centred  
15 relative to the needle 1, the characteristics of the needle become independent or at least less dependent on how the needle is rotated about its longitudinal centre line 5 when a membrane 2 is penetrated. In other words, the penetrating tip 4 will impact substantially the same point on the membrane when the membrane is repeatedly penetrated even in the case  
20 when the needle is rotated about its longitudinal axis between penetration occasions. This means that the needle will always impact the membrane in the centre of the needle-membrane system resulting in a favourable load distribution on the membrane during penetration thereof, thereby reducing the risk of the membrane cracking adjacent to the penetration hole. Furthermore, in addition to the advantages already described the transport of membrane material into the needle is further obstructed.

25

Furthermore, the pointed end is provided with an opening 6 for letting a liquid in and/or out in a main direction 7 which is substantially parallel to the longitudinal extension of the needle 1. Such a flow direction in the forward direction is an absolute necessity in many medical systems where the needle is included, for avoiding flushing against other adjacent  
30 equipment, where otherwise the function of such equipment may be affected by the liquid in an undesirable way. Furthermore, such a flow direction in the forward direction may also enhance mixing of the current drug, such as for example a powdered substance. Although the opening 6 is arranged on substantially one and the same half of the cross section of the needle, and on the upper side of the longitudinal centre line of the needle 5 such as illustrated in Fig. 1, primarily for reasons associated with the manufacturing of the needle, it  
35

would be possible to locate one or more openings in other positions relative to the cross section of the needle 1, while maintaining the desired main direction of the flow.

5 The opening 6, which is located in the pointed end 3 of the needle 1, is intended to enable a liquid to be transferred to or from the needle 1. For example, the needle 1 may be inserted through a membrane which constitutes a seal of a container, such as a medicine bottle, for drawing the contents in the container up and then, in a similar way, the needle may penetrate a second membrane of a second container, such as an infusion bag, for transferring the contents previously drawn up to this second container.

10


15 The penetrating tip 4 of the needle 1 according to the invention is designed with a substantially point-shaped edge 8 to initially prick a membrane when the membrane is penetrated. Furthermore, the outer edges 19 present on the pointed end 3 in the area between the point-shaped edge 8 and a position 25 beyond the opening 6 are rounded to ensure that, after the initial penetration, the pointed end 3 will push the membrane material away rather than cutting the membrane material when the membrane is penetrated.

20 In Fig. 2a an example of a possible cross section of the outermost penetrating tip 4 is illustrated. Although the penetrating tip 4 is illustrated in Fig. 2a with a triangular cross section with rounded corners, other symmetries are possible such as a substantially circular cross section. The triangular symmetry gives rise to three substantially equally sized forces affecting the membrane in different directions and radial to the longitudinal extension of the needle. Since the forces co-interact each other, the needle will act in a self-centring way during penetration of the membrane.

25

30 The pointed end 3 has suitably a shape substantially corresponding to a part of an imaginary cone, the tip 9 of which coincides with the substantially point-shaped edge 8. By creating a conical shape of the outermost part of the pointed end 3, preferably having a substantially triangular or circular cross section, the desired edge is obtained, which edge has the function to initially prick the membrane and, when penetration continues, the pointed end 3 will push the membrane material away, primarily in directions substantially perpendicular to the longitudinal extension of the needle, instead of cutting the membrane material, such as usual, when the subsequent part of the needle passes through the membrane. This means that, instead of cutting the membrane, the elasticity of the membrane is utilised to enable penetration of the membrane. Thus, the damaging of the membrane by forming a cut,

35





having an extension the size of the diameter of the needle, as being characteristic for prior art needles, is avoided.

5 To achieve a pointed end 3 without cutting edges, the needle 1 may for example be ground and/or blasted and/or electrochemically polished to obtain the desired shape and surface smoothness and to remove possibly burrs located for example around the opening 6.

10 The invention also relates to an arrangement for transferring a liquid, comprising a membrane 2 and a needle 1 according to the invention for penetrating the membrane. The liquid may be transferred from inside the needle to a volume sealed by the membrane or in the opposite direction from the volume to the inside of the needle.

15 The needle according to the invention may be produced from a stainless steel, such as for example Stainless steel AISI 304, but also other material are possible, such as plastic for instance. With the exception of the pointed end 3 of the needle, the needle may be designed according to general standards, for example with an outer diameter of approximately 1.2 mm and an inner diameter of approximately 0.9 mm. In Fig. 1, the membrane 2 is also schematically illustrated, which membrane suitably is produced from a thermoplastic elastomer (TPE), though a silicone rubber is also a possible material of the membrane, and  
20 which membrane has a thickness 10 in the interval from parts of a millimetre to several millimetres, for example up to 10-15 mm or more, and preferably about 3 mm.

25 It is not unlikely that a needle 1 according to the invention, which has been designed so that at least in some respects it is blunt as compared to a conventional needle, requires that a larger force be used when the membrane is penetrated. However, this is not particularly critical, since the needle is not intended to penetrate directly in skin and/or tissue of a patient and, thereby, the problem of minimising pain inflicted on the patient to the greatest possible extent is not present. Instead, such as previously described, the primary aim is to minimize the damage of the membrane 2 to the greatest possible extent to thereby avoid  
30 possible leakage and contamination when the membrane is penetrated.

In Fig. 3, a membrane is depicted which has been penetrated by a needle having a relatively wide cutting edge in accordance with prior art. A number of cuts 11 have been created when the membrane 2 was penetrated and, furthermore, it is illustrated how a part 12 of the

membrane 2 thereby has been cut out and runs the risk of coming loose from the membrane and leading to contamination of the system.

5 In Figs. 4 and 4a, a membrane is depicted which has been penetrated by a needle 1 according to the invention having a substantially point-shaped edge 8. In the example illustrated in 4a, the penetrations have been performed at different locations 13 on the membrane 2. Nevertheless, such as described above, if the point-shaped edge 8 of the penetrating tip 4 is arranged to lie substantially on the longitudinal centre line 5 of the needle 1 and the position of the centre line 5 of the needle relative to the membrane is 10 substantially maintained between the penetrations, penetration may be performed at one and the same point 13 of the membrane, as illustrated in Fig. 4, even if the needle has been rotated about its own longitudinal axis. In the case illustrated in Fig. 4a, however, it is assumed that one or more penetrations have been performed at several locations 13 on the membrane 2.

15 If the point-shaped edge 8 is centred as described above, only one point-shaped hole 13 of the membrane 2 is formed as a consequence of several penetrations. Ideally, only such a through hole is formed when the membrane 2 is penetrated, but depending on the properties of the membrane, for example thickness, elasticity, etc., the load from the needle 20 may also cause the membrane 2 to crack 14 adjacent to the penetration hole 13, such as illustrated for some of the penetration positions. However, it should be emphasised that these crack formations 14 are not in any way comparable to the cut cuts 11 according to Fig. 3, which necessarily arise when needles according to prior art are used. However, most often the crack formation 14 which in some cases may arise when the needle according to 25 the invention is used is not desired, and consequently, the characteristics of the needle 1 and the membrane 2 are suitably adapted to each other so that these cracks 14 are avoided and/or delimited as regards the size to the greatest possible extent, for example by choosing a membrane material having sufficient elasticity.


30 In Figs. 5-10 there is illustrated how a needle 1 may be manufactured in accordance with the method according to the invention. In a first step illustrated in Fig. 5 and 7, a tubular blank 15 is obliquely cut, which blank 15 preferably has a circular cross section, to obtain a pointed end 3. The thus obtained pointed end 3 of the needle has an opening 6 constituting an inlet and/or outlet of a through channel 16 in the needle 1 for transport of fluid.

35

The pointed end 3 is then shaped so that the outermost portion of the tip, which tip is intended to constitute a penetrating tip 4 when a membrane is penetrated, lies substantially on the longitudinal centre line 5 of the tubular blank, i.e. the needle 1. For this purpose, the tip 4 is bent suitably from a position 17 located at the periphery of the needle (see Fig. 6), where the tip has a position 17 depicted by dot-dashed lines in a lower part of the needle 1, in the direction towards (upwards in Fig. 6) a position in which the tip occupies substantially the centre of a cross section of the needle. A further adjustment of the position of the tip 4 may, if so is desired, be performed in connection with the tip 4 being shaped to the desired shape in for example a subsequent grinding step.


All outer edges 19 present on the penetrating tip 4 are rounded or chamfered for forming a substantially point-shaped edge 8 according to Figs. 1 and 2 and removing the sharp edges possibly occurring closest to the point-shaped edge 8, which edges otherwise would cut the membrane material when the membrane is penetrated. Suitable methods for removing sharp edges is to blast the pointed end 3 or to use electrochemical polishing. To give the tip 4 a basic shape and/or reduce the need of extensive surface treatment, such as blasting, the tip 4 may first be ground, for example it may be provided with a so-called back bevel cut, and thereafter the required surface treatment in the form of blasting or electrochemical polishing or any similar method is performed. Preferably all surfaces 18 and edges 19 of the pointed end 3, comprising the penetrating tip 4, in the area between the point-shaped edge 8 and a position 25 beyond the opening 6, are treated with for example blasting to shape the tip further and remove possibly sharp edges and burrs to give the needle the desired features. Furthermore, advantageously the inner edge 21, at least the rear portion of the inner edge 21 of the opening 6, is also treated with for example blasting.

In Figs. 8, 9 and 10, such a back bevel cut mentioned above which may be performed before blasting is illustrated. Furthermore, the needle is illustrated before a possible bending of the tip to the centre line, since it is often easier to grind the tip before bending thereof. The grinding is accomplished primarily on the underside 20 of the pointed end 3 of the needle 1 in such a way that, when the needle is seen from above, such as is the case in Fig. 9, a conical shape of the penetrating tip is obtained. Preferably, the pointed end 3 is provided with a first grind angle, i.e. a tip angle  $\alpha$ , in the interval 50 to 100° and a second grind angle  $\beta$  in the interval 50 to 140°. In the illustrated example, the needle has been ground to the angles  $\alpha=75^\circ$  and  $\beta=100^\circ$ , but it should be emphasised that the way of grinding as well as the grinding angles, during the optional grinding step, may be varied in many different ways



within the scope of the invention and furthermore that it is the final shape of the needle having a point-shaped edge 8 and a rounded tip 4 without cutting edges that is the basic idea of the invention. Although a back bevel cut is preferably used to give the needle the basic form prior to the rounding of the needle, other grinding operations providing the  
5 needle with other cuts such as for example a lancet bevel cut are also possible.

Thus, it is emphasised that the needle according to the invention, the arrangement for transferring a liquid according to the invention and the method according to the invention are not limited by the embodiments of the invention described above, but only by the scope  
10 of the following claims. Once the idea of the invention is known, several modifications within the scope of the invention could then be obvious to a man skilled in the current technical field.



CLAIMS

- 5 1. A needle (1) for penetrating a membrane (2), having a pointed end (3) provided with a penetrating tip (4) and with an opening (6) for letting a liquid in and/or out in a main direction (7) which is substantially parallel to the longitudinal extension of the needle, **characterized in that** the penetrating tip (4) is designed with a substantially point-shaped edge (8) to initially prick a membrane (2) when the
- 10 membrane is penetrated and that the outer edges (19) present on the pointed end (3) in the area between the point-shaped edge (8) and a position (25) beyond the opening (6) are rounded so that after the initial penetration the pointed end (3) will push the membrane material away rather than cutting the membrane material.
- 15 2. A needle according to claim 1, **characterized in that** the inner edge (21) of the opening (6) is rounded.
- 20 3. A needle according to claim 1 or 2, **characterized in that** the penetrating tip (4) is designed with a cross section (26) having a symmetry causing at least three substantially equally sized forces (F) in different directions which are radial to the longitudinal centre line (5) of the needle and which forces counteract each other so that the needle (1) will tend not to deviate from the initial penetration direction when the needle (1) penetrates a membrane (2).
- 25 4. A needle according to claim 3, **characterized in that** the cross section is triangular with rounded edges.
- 30 5. A needle according to claim 3, **characterized in that** the cross section is circular.
- 35 6. A needle according to any of claims 1-5, **characterized in that** the point-shaped edge (8) of the penetrating tip (4) is arranged to lie substantially on the longitudinal centre line (5) of the needle (1).
7. A needle according to any of claims 1-6, **characterized in that** the pointed end (3) has a shape substantially corresponding to a part of an imaginary cone, the

tip (9) of which coincides with the substantially point-shaped edge (8).

8. A needle according to any of claims 1-7, **characterized in that** at least a major part of the opening (6) is arranged on one and the same half of the cross section of the needle (1).
9. A needle according any of claims 1-8, **characterized in that** the pointed end (3) is provided with a basic shape in accordance with a lancet bevel cut.
10. A needle according any of claims 1-8, **characterized in that** the pointed end (3) is provided with a basic shape in accordance with a back bevel cut.
11. A needle according to claim 10, **characterized in that** the back bevel cut has a tip angle ( $\alpha$ ) in the interval 50° to 100°.
12. A needle according to claim 11, **characterized in that** the tip angle ( $\alpha$ ) is approximately 75°.
13. A needle according any of claims 10-12, **characterized in that** the back bevel cut has a second grind angle ( $\beta$ ) in the interval 50° to 140°.
14. A needle according to claim 13, **characterized in that** the second grind angle ( $\beta$ ) is approximately 100°.
15. An arrangement for transferring a liquid, comprising a membrane (2) and a needle (1) for penetrating the membrane (2), said needle (1) having a pointed end (3) provided with a penetrating tip (4) and with an opening (6) for letting a liquid in and/or out in a main direction (7) which is substantially parallel to the longitudinal extension of the needle (1), **characterized in that** the penetrating tip (4) is designed with a substantially point-shaped edge (8) to initially prick a membrane (2) when the membrane is penetrated and that the outer edges (19) present on the pointed end (3) in the area between the point-shaped edge (8) and a position (25) beyond the opening (6) are rounded so that after the initial penetration the pointed end (3) will push the membrane material away rather than cutting the membrane material.

16. An arrangement according to claim 15, **characterized in that** the inner edge (21) of the opening (6) is rounded.
- 5 17. An arrangement according to claim 15 or 16, **characterized in that** the penetrating tip (4) is designed with a cross section (26) having a symmetry causing at least three substantially equally sized forces (F) in different directions which are radial to the longitudinal centre line (5) of the needle and which forces counteract each other so that the needle (1) will tend to not deviate from the  
10 initial penetration direction when the needle (1) penetrates a membrane (2).
18. An arrangement according to claim 17, **characterized in that** the cross section is triangular with rounded corners.
- 15 19. An arrangement according to claim 17, **characterized in that** the cross section is circular.
- 20 20. An arrangement according to any of claims 15-19, **characterized in that** the point-shaped edge (8) of the penetrating tip (4) is arranged to lie substantially on the longitudinal centre line (5) of the needle (1).
- 25 21. An arrangement according to any of claims 15-20, **characterized in that** the pointed end (3) has a shape substantially corresponding to a part of an imaginary cone, the tip (9) of which coincides with the substantially point-shaped edge (8).
22. An arrangement according to any of claims 15-21, **characterized in that** at least a major part of the opening (6) is arranged on one and the same half of the cross section of the needle (1).
- 30 23. An arrangement according any of claims 15-22, **characterized in that** the pointed end (3) is provided with a basic shape in accordance with a lancet bevel cut.
- 35 24. An arrangement according any of claims 15-22, **characterized in that** the pointed end (3) is provided with a basic shape in accordance with a back bevel

cut.

- 5
25. An arrangement according to claim 24, **characterized in that** the back bevel cut has a tip angle ( $\alpha$ ) in the interval 50° to 100°.
26. An arrangement according to claim 25, **characterized in that** the tip angle ( $\alpha$ ) is approximately 75°.
- 10 27. An arrangement according any of claims 24-26, **characterized in that** the back bevel cut has a second grind angle ( $\beta$ ) in the interval 50° to 140°.
28. An arrangement according to claim 27, **characterized in that** the second grind angle ( $\beta$ ) is approximately 100°.
- 15 29. A needle for penetrating a membrane (2), said needle (1) having a pointed end (3) provided with a penetrating tip (4) and with an opening (6) for letting a liquid in and/or out in a main direction (7) which is substantially parallel to the longitudinal extension of the needle (1), **characterized in that** the penetrating tip (4) is designed with a cross section (26) having a symmetry causing at least
- 20 three substantially equally sized forces (F) in different directions which are radial to the longitudinal centre line (5) of the needle and which forces counteract each other so that the needle (1) will tend not to deviate from the initial penetration direction when the needle (1) penetrates a membrane (2).
- 25 30. A needle according to claim 29, **characterized in that** the cross section is triangular with rounded corners.
31. A needle according to claim 29, **characterized in that** the cross section is circular.
- 30 32. A needle according to any of claims 29-31, **characterized in that** the point-shaped edge (8) of the penetrating tip (4) is arranged to lie substantially on the longitudinal centre line (5) of the needle (1).
- 35 33. A method for manufacturing a needle (1) for penetrating a membrane (2),



comprising:

cutting a tubular blank (15) obliquely for obtaining a pointed end (3) provided with a penetrating tip (4) and with a opening (6) for letting a liquid in and/or out in a main direction (7) which is substantially parallel to the longitudinal extension of the needle (1),

**characterized by** providing the penetrating tip (4) with a substantially point-shaped edge (8), and

rounding all outer edges (19) present on the pointed end (3) in the area between the point-shaped edge (8) and a position (25) beyond the opening (6).

34. A method according to claim 33, **characterized by** rounding the inner edge (21) of the opening (5).

35. A method according to claim 33 or 34, **characterized by** shaping the penetrating tip (4) with a cross section (26) having a symmetry causing at least three substantially equally sized forces (F) in different directions which are radial to the longitudinal centre line (5) of the needle (1) and which forces counteract each other so that the needle (1) will tend not to deviate from the initial penetration direction when the needle (1) penetrates a membrane (2).

36. A method according to any of claims 33-35, **characterized by** arranging the point-shaped edge (8) of the penetrating tip (4) to lie substantially on the longitudinal centre line (5) of the needle (1).

37. A method according to any of claims 33-36, **characterized by** shaping the pointed end (3) as a part of an imaginary cone, the tip (9) of which coincides with the substantially point-shaped edge (8).

38. A method according to any of claims 33-37, **characterized by** shaping the pointed end (3) so that at least a major part of the opening (6) will be located on one and the same half of the cross section of the needle (1).

Ink. t. Patent- och reg.verket

2003 -01- 2 1

Huvudföretag Kassa

17

39. A method according to any of claims 33-38, **characterized by** grinding the penetrating tip (4) in accordance with a lancet bevel cut before rounding the outer edges of the pointed end (3).

5

40. A method according to any of claims 33-38, **characterized by** grinding the penetrating tip (4) in accordance with a back bevel cut before rounding the outer edges of the pointed end (3).

10

41. A method according to any of claims 33-40, **characterized by** rounding the outer edges (19) by blasting and/or electrochemical polishing.

42. A method according to any of claims 33-41, **characterized by** rounding the inner edge (21) of the opening (6) by blasting and/or electrochemical polishing.

15

20

25

30


35





ABSTRACT

A needle 1 for penetrating a membrane 2, having a pointed end 3 provided with a penetrating tip 4 and with an opening 6 for letting a liquid in and/or out in a main direction 7  
5 which is substantially parallel to the longitudinal extension of the needle 1. The penetrating tip 4 is designed with a substantially point-shaped edge 8 to initially prick the membrane when the membrane is penetrated. The outer edges 19 present on the pointed end 3 in the area from the point-shaped edge 8 to a position beyond the opening 6 are rounded so that  
10 after the initial penetration the pointed end 3 will push the membrane material away rather than cutting the membrane material.

(Fig. 1)



1/4







FIG. 2a



PRIOR ART  
FIG.3




FIG. 4




FIG. 4a




FIG. 5




FIG. 6




FIG. 7

00001551




FIG. 8




FIG. 9




FIG. 10